## **Amendments**

## Amendment to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

Claim 1. (Currently amended) Silanised, structurally modified <u>pyrogenically produced</u> silicas, <u>characterised characterized</u> by vinyl groups or vinyl silyl groups fixed to the surface, hydrophobic groups such as trimethyl silyl and/or dimethyl silyl and/or monomethyl silyl additionally being fixed to the surface, having the following physico-chemical properties:

BET surface area  $m^2/g$ : 25 - 400

Average primary

particle size nm: 5 - 50 pH: 3-10

Carbon content %: 0.1-10

DBP value %: < 200 or not determinable.

- Claim 2. (Currently amended) The process for producing the silanised, structurally modified silicas according to claim 1, comprising <u>a</u>) treating <u>pyrogenically produced</u> silicas with a surface-modifying agent to form a mixture, <u>b</u>) heat treating the mixture and then <u>c</u>) structurally modified modifying the heat treated mixture by mechanical action.
- Claim 3. (Previously presented) The process for producing the silanised, structurally modified silicas according to claim 2, wherein the silica treating step includes spraying the silicas first with water and then with the surface-modifying agent.
- Claim 4. (Previously presented) The process for producing the silanised, structurally modified silica according to claim 2, wherein the silica treating step includes treating the silica with the

- surface-modifying agent in vapour form.
- Claim 5. (Currently amended) The process for producing the silanised, structurally modified silica according to claim 3, further comprising <u>post-grinding post-grounding</u> and/or conditioning the structurally modified silica.
- Claim 6. (Previously presented) The process for producing the silanised, structurally modified silica according to claim 4, further comprising grinding and/or conditioning the structurally modified silica.
- Claim 7. (Currently amended) A silicone rubber containing <u>as</u> a filler <del>wherein the improvement</del> <del>comprises</del> the silanised, structurally modified silica according to claim 1 <del>as the filler</del>.
- Claim 8. (Previously presented) The process according to claim 3 further comprising, prior to heat treatment step, further mixing the treated silica mixture.